INLINE2000/A

NEGATIVE AIR MACHINES

The Reliable Choice for Abatement Contractors

Key features Include: High CFM; Three Stages of Filtration & Easy Filter Removal

The INLINE2000 AND INLINE2000A Negative Air Machines are perfect for contractors who want the very best in performance, reliability and quality.

FEATURES & BENEFITS

- One-horsepower, two speed motor delivers airflow of 1,900 on High and 1,200 on Low (cfm)
- At only 26 inches wide the INLINE2000 and INLINE2000A fit easily through standard doorways
- Four heavy-duty, 4" casters (2 fixed and 2 locking swivels) provide mobility and maneuverability
- Standard filters include: 1 ea. polypad prefilter, 1 ea. pleated prefilter and 1 ea. 99.97% tested HEPA filter
- INLINE2000 is equipped with a visual "change filter" indicator lamp
- INLINE2000A is equipped with a differential pressure gauge and an audio "Change Filter" alarm
- The INLINE2000/A have been independently tested and certified in accordance with applicable UL and CSA safety requirements

INLINE2000 SKU: 402139
INLINE2000A SKU: 402140







TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	INLINE2000/A
Net Weight	lbs. (kg)	120 (56.25)
Dimensions (L x W x H)	in. (cm)	36 x 26 x 30.4 (91 x 66 x 77)
Electrical Rating	V, Hz, A	120 VAC, 60 Hz, 15 A
Airflow, max. with clean filters	CFM	1,900 High Speed, 1,200 Low Speed
Normal Operating Amps	amps	10
Motor	-	1 HP, 2 speed motor with thermal overload protection, auto re-set, 60 Hz, single phase
Sound Level @ 5 Feet	dBA	70 on high speed
Cabinet Material	-	20 Gauge galvanized steel
HEPA Filter Efficiency	-	99.97% @ 0.3 microns
Prefilter Access	-	Slide out grill
First Stage Prefilter	1 ea.	Polypad, SKU: 050031
Second Stage Prefilter	1 ea.	2" deep particulate pleat, SKU: 050045/050075
Alternate Second Stage	-	2" deep high capacity carbon, SKU: 050060
HEPA Filter	1 ea.	6" deep, plastic frame, cert. 2000 CFM, tested 99.97%, SKU: 050065
Alternate HEPA Filter	1 ea.	12" deep, wood frame, cert. 1000 CFM, 99.97%, SKU: 050047

Specifications and details are subject to change without prior notice.

Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.

INLINE 2000
(800)795-0933 • inlineco.com

THE INLINE2000/A IS BEST SUITED FOR:

- ABATEMENT & REMEDIATION
- HEALTH CARE CONSTRUCTION